

NOTES:

1. DIE THICKNESS ALLOWABLE IS 0.305mm MAXIMUM(.012 INCHES MAXIMUM)
2. DIMENSIONING & TOLERANCES CONFORM TO ASME Y14.5M. – 1994.
3. N IS THE NUMBER OF TERMINALS.
4. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30mm FROM TERMINAL TIP.
5. THE PIN #1 IDENTIFIER MUST BE EXISTED ON THE TOP SURFACE OF THE PACKAGE BY USING INDENTATION MARK OR OTHER FEATURE OF PACKAGE BODY.
6. EXACT SHAPE AND SIZE OF THIS FEATURE IS OPTIONAL.
7. ALL DIMENSIONS ARE IN MILLIMETERS.
8. UNILATERAL COPPLANARITY ZONE APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
9. APPLIED ONLY FOR TERMINALS.

S <sub>y</sub> M <sub>B</sub> L	COMMON DIMENSIONS			N <sub>O</sub> T <sub>E</sub>
	MIN.	NOM.	MAX.	
A	—	0.85	0.90	
A1	0.00	0.01	0.05	8
A2	—	0.70	0.75	
A3	0.15 REF.			
D	10.00 BSC			
D1	9.74 BSC			
E	10.00 BSC			
E1	9.74 BSC			

S <sub>y</sub> M <sub>B</sub> L	PITCH VARIATION			N <sub>O</sub> T <sub>E</sub>
	MIN.	NOM.	MAX.	
eT	0.50 BSC			
eR	0.65 BSC			
N	124			3
Nd <sub>d</sub>	16			3
NDb	15			3
NE <sub>d</sub>	16			3
NE <sub>b</sub>	15			3
L <sub>q</sub>	0.30	0.40	0.50	
L <sub>b</sub>	0.30	0.40	0.50	
b	0.17	0.22	0.27	4
D2	6.80	6.90	7.00	
E2	6.80	6.90	7.00	
θ	—			12°
P	0.24	0.42	0.60	



www.amkor.com

TITLE PACKAGE OUTLINE, DUAL ROW M.F. 124 LEAD,  
10 X 10 mm BODY, ETCHED, 0.50/0.65 mm LEAD PITCH,  
INTERSTITIAL TYPE, PUNCH SINGULATION

FORM NO.	MBF_LT_7JLWNG	DATE	31/2009	REV	00
PRINTING IS AN ACTUAL SCALE		SCALE	1:1		
FORM NO.	MBF_LT_7JLWNG	DATE	001-0000-3817		
REV	A3	REV	N/A	REV	
REV	N/A	REV		REV	

THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF AMKOR. THE INFORMATION, DRAWINGS AND DESIGN CONTAINED HEREIN ARE CONFIDENTIAL/PROPRIETARY AND SHALL NOT BE RELEASED TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMKOR.