

NOTES:

1. DIE THICKNESS ALLOWABLE IS 0.305mm MAXIMUM(.012 INCHES MAXIMUM)
2. DIMENSIONING & TOLERANCES CONFORM TO ASME Y14.5M. – 1994.
3. N IS THE NUMBER OF TERMINALS.
4. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30mm FROM TERMINAL TIP.
5. THE PIN #1 IDENTIFIER MUST BE EXISTED ON THE TOP SURFACE OF THE PACKAGE BY USING INDENTATION MARK OR OTHER FEATURE OF PACKAGE BODY.
6. EXACT SHAPE AND SIZE OF THIS FEATURE IS OPTIONAL.
7. ALL DIMENSIONS ARE IN MILLIMETERS.
8. UNILATERAL COPLANARITY ZONE APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.
9. APPLIED ONLY FOR TERMINALS.

| S _Y M _B L | COMMON DIMENSIONS | | | N _O T _E |
|---------------------------------------|-------------------|------|------|-------------------------------|
| | MIN. | NOM. | MAX. | |
| A | — | 0.85 | 0.90 | |
| A1 | 0.00 | 0.01 | 0.05 | 8 |
| A2 | — | 0.70 | 0.75 | |
| A3 | 0.15 REF. | | | |
| D | 10.00 BSC | | | |
| D1 | 9.74 BSC | | | |
| E | 10.00 BSC | | | |
| E1 | 9.74 BSC | | | |

| S _Y M _B L | PITCH VARIATION | | | N _O T _E |
|---------------------------------------|-----------------|------|------|-------------------------------|
| | MIN. | NOM. | MAX. | |
| eT | 0.50 BSC | | | |
| eR | 0.65 BSC | | | |
| N | 132 | | | 3 |
| NDd | 18 | | | 3 |
| NDb | 15 | | | 3 |
| NEd | 18 | | | 3 |
| NEb | 15 | | | 3 |
| Ld | 0.30 | 0.40 | 0.50 | |
| Lb | 0.30 | 0.40 | 0.50 | |
| b | 0.17 | 0.22 | 0.27 | 4 |
| D2 | 6.80 | 6.90 | 7.00 | |
| E2 | 6.80 | 6.90 | 7.00 | |
| θ | — | | | 12° |
| P | 0.24 | 0.42 | 0.60 | |



TITLE PACKAGE OUTLINE, DUAL ROW M.L.F. 132 LEAD,
10 X 10 mm BODY, ETCHED, 0.50/0.65 mm LEAD PITCH,
INTERSTITIAL TYPE, PUNCH SINGULATION

| | | | | | |
|-----------------------------|---------------|-------|---------------|-----|----|
| FORM NO. | MBF_LT_7JLWNG | DATE | 31.4.327 | REV | OC |
| PRINTING IS AN ACTUAL SCALE | | SCALE | 1:1 | | |
| FORM NO. | MBF_LT_7JLWNG | DATE | 001-0000-3817 | | |
| FORM NO. | MBF_LT_7JLWNG | DATE | 001-0000-3817 | | |

THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE THE EXCLUSIVE PROPERTY OF AMKOR TECHNOLOGY. NO PARTS, INFORMATION, DRAWINGS AND DESIGN CONCEPTS CONTAINED HEREIN ARE TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMKOR TECHNOLOGY.

12 11 10 9 8 7 6 5 4 3 2 1